

noise level of 5%. When the level of noise is very high its results are the worst. Our proposed clustering-based edge detector produces as good result as Canny at lower level of noises. But it shows more resilience to very high level of noise. From the figures, we can observe that result by our method at 30% of noise level is better than that by Canny. However, we acknowledge that our method incurs some small islands of false edges that Canny does not.

For the images corrupted with Gaussian noises, Sobel fairs better but Canny performs worse than before. However, the performances of both methods are worse than our proposed method as can be clearly observed in the figures.

5 Conclusion

The results presented in this paper are preliminary but are sufficient enough to show that using variance, entropy, gradient, and busyness values of the image pixel as features for k-means clustering coupled with silhouette analysis is a good method for detecting edge for noisy images. As for future work, we will try to find out better filtering techniques to remove the small islands of false edges from our results. We also plan to modify our algorithm to detect edges from color images directly without converting it to grayscale.

References

- [1] W. Dai and K. Wang, "An image edge detection algorithm based on local entropy," in *Proceedings of the IEEE International Conference on Integration Technology (ICIT'07)*, 2007, pp. 418–420.
- [2] J. F. Canny, "Computational approach to edge detection," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 8, 1986, pp. 679–698.
- [3] W. L. Woon, P. Liatsis, and K. D. Wong, "Fusion Of multiple edge maps for improved noise resistance," in *Proceedings of MMU International Symposium of Information and Communication Technologies (M2USIC'06)*, 2006, pp. 1–8,
- [4] Y. Becerikli, H. E. Demiray, M. Ayhan, and K. Aktas, "Alternative neural network based edge detection," *Neural Information Processing – Letters and Reviews*, vol. 10, 2006, pp. 193–199.
- [5] N. A. M. Isa, "Automated edge detection technique for pap smear images using moving k-means clustering and modified seed based region growing algorithm," *International Journal of the Computer, the Internet and Management*, vol. 13, 2005, pp. 45–59.
- [6] Y. Zhai and X. Liu, "Multiscale edge detection based on fuzzy c-means clustering," in *Proceedings of the 1st International Symposium on Systems and Control in Aerospace and Astronautics (ISSCAA'06)*, 2006, pp. 1201–1204.
- [7] J. Li and Z. Lei, "Adaptive thresholds edge detection for defective parts images based on wavelet transform," in *Proceedings of the 2011 International Conference on Electric Information and Control Engineering (ICE-ICE'11)*, 2011, pp. 1134–1137.
- [8] D. Ganguly, S. Mukherjee, K. Mitra, and P. Mukherjee, "A novel approach for edge detection of images," in *Proceedings of the International Conference on Computer and Automation Engineering (ICCAE'09)*, 2009, pp. 49–53.
- [9] I. E. Sobel, *Camera Models and Machine Perception*, Ph.D. Thesis, Electrical Engineering Department, Stanford University, California, United States, 1970.
- [10] P. A. Dondes and A. Rosenfeld, "Pixel classification based on gray level and local "Busyness";," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 4, 1982, pp. 79–84.
- [11] P. J. Rousseeuw, "Silhouettes: a graphical aid to the interpretation and validation of cluster analysis," *Computational and Applied Mathematics*, vol. 20., 1987, pp. 53–65.